



PIN NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14
SIGNAL	VDD	VSS	VO	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7

- NOTES:
- 1.DISPLAY TYPE: FSTN
 - 2.VIEWING ANGLE: 6:00
 - 3.POLARIZER MODE:TRANSMISSIVE/NEGATIVE
 - 4.OPERATING TEMP: -20°C ~ +70°C
 - 5.STORAGE TEMP: -30°C ~ +80°C
 - 6.LOGIC VOLTAGE: VDD=5.0V
 - 7.LCD DRIVER VOLTAGE: Vop=4.5V
 - 8.DRIVE METHOD: 1/16DUTY 1/4BIAS
 - 9.DRIVE IC: S6A0069
 - 10.BACKLIGHT TYPE: GREEN EDGE LED

NITERAY ELECTRONIC & PLASTIC CO., LTD.

DRAW NO.	YMFC-C1602DDNSYSN	DRAWN	ME CHECKED	EE CHECKED	APPROVED
UNIT:mm	PAGE:1/1	VER: B	SCALE:1/1		
REV.	DESCRIPTION	DATE	TOLERANCES UNLESS:±0.3		

REV.	DESCRIPTION	DATE